

# RECESSED LOW PROFILE PREMIUM

## FEATURES - CUSTOM for 30" x 30" grid

**LED Premium** Recessed ceiling fixture ideal for offices & retail, requiring higher lumen output & better distribution. Sleek contemporary appearance.

**CONSTRUCTION** Die-formed of heavy-duty 24 ga. pre-painted steel with parabolic BWE reflector. Accessplate on the top allows for quick easy wiring. Custom optics enhance performance & efficiency.

**LENS** High-efficient moulded acrylic **6" wide** semi-frosted linear diffuser for optimum distribution and performance.

**COLOURS & CRI** Available in 3000K, 3500K, 4000K, 5000K. Optional 6500K. 82 CRI is standard.

**OPERATION** -20°C to 40°C (-40°C optional) L70 at 50,000 hrs. with 5 yr. warranty; L70 at 100,000 hrs. with 10 yr. warranty.


**ELECTRICAL** Available in 120V, UNV, or 347V. Thermally protected driver. 0-10v dimming standard.

**LISTINGS** CSA for Canada & US.



**NOTE** Due to continuing improvements in LED technology, specifications are subject to change.

### Ordering Information

MODEL (W x L)	LUMENS '000's	COLOUR	VOLTS	OPTIONS	TO ORDER
R TBS-3030-W	3 4 5 6	3K	120	<b>W</b> WIDE lens	Start with model, add lumens, colour, voltage, & options.
		35K	277	<b>PWD</b> Pre-wired dimming	
		4K	347	<b>EM</b> Emergency pack	
		5K	UNV (120-277v)	<b>CT</b> -40C min. start	
				<b>AH</b> Air slots	
		 C US		<b>Example:</b>	R TBS-3030-W-6L-40K-120
					30"x 30" fixture, 6000 lumens, 4000k colour, 120V

LUMENS Nominal	Approx. Delivered	WATTS	LPW Del'd
----------------	-------------------	-------	-----------

3,000	3,124	28	112
4,000	3,626	29	125
5,000	4,848	40	121
6,000	5,623	48	117

Please consult factory for additional lumen packages and options

\*\* Also available in 750mm x 750mm metric size. Consult factory \*\*

Data tolerances: flux  $\pm 7.5\%$ ; efficacy  $\pm 10\%$

NOTE: Lumen packages may vary slightly with different components

R TBS-30-W Profile View

